

AOXUAN SLEWING RING 110

No.	Ring Dimension				Mounting Dimension					Structure Dimension				N.W	
DL	De	D	d	H	D1	D2	n	φ	M	n	D3	d1	H1	h	kg
mm	mm	mm	mm	mm	mm	mm	n	m	m	1	mm	mm	mm	m	
110.25.500		602	398	75	566	434	20	18	16	4	498	502	65	10	77
110.25.560		662	458	75	626	494	20	18	16	4	558	562	65	10	87
110.25.630		732	528	75	696	564	24	18	16	4	628	632	65	10	95
110.25.710		812	608	75	776	644	24	18	16	4	708	712	65	10	111
110.28.800		922	678	82	878	722	30	22	20	6	798	802	72	10	167
110.28.900		1022	778	82	978	822	30	22	20	6	898	902	72	10	186
110.28.1000		1122	878	82	1078	922	36	22	20	6	998	1002	72	10	204
110.28.1120		1242	998	82	1198	1042	36	22	20	6	1118	1122	72	10	233
110.32.1250		1390	1110	91	1337	1163	40	26	24	5	1248	1252	81	10	337
110.32.1400		1540	1260	91	1487	1313	40	26	24	5	1398	1402	81	10	369
110.32.1600		1740	1460	91	1687	1513	45	26	24	5	1598	1602	81	10	425
110.32.1800		1940	1660	91	1887	1713	45	26	24	5	1798	1802	81	10	525
110.40.2000		2178	1825	112	2110	1891	48	33	30	8	1997	2003	100	12	815
110.40.2240		2418	2065	112	2350	2131	48	33	30	8	2237	2243	100	12	944
110.40.2500		2678	2325	112	2610	2391	56	33	30	8	2497	2503	100	12	1026
110.40.2800		2978	2625	112	2910	2691	56	33	30	8	2797	2803	100	12	1375
110.50.3150		3376	2922	134	3286	3014	56	45	42	8	3147	3153	122	12	2097