

Double-ROW Slewing Ring (Series 02)

No.	Type			Configuration & Structural Dimension									Mounting Hole Dimension						Gear Parameter				Weight												
	020	021,022	023,024	D	d	H	H1	h	020,023,024		021,022		n1	D1	D2	n	Type 0			Type 1,2,3			b	m	021,022		023,024		020	021,022	023,024				
	Steel Ball Spec. DL								D3	d1	D3	d1					φ	M	T	z	da	z			da	kg									
1	020.25.500	021.25.500 022.25.500	023.25.500 024.25.500	616	384	106	96	26	482	477	523	518	4	580	420	20	φ18	16	32	60	5	126	664	72	357	121	130	126							
2	020.25.560	021.25.560 022.25.560	023.25.560 024.25.560	676	444	106	96	26	543	537	583	578	4	640	480	20	φ18	16	32	60	5	138	704	64	417	136	146	143							
3	020.25.630	021.25.630 022.25.630	023.25.630 024.25.630	746	514	106	96	26	613	607	653	648	4	710	550	24	φ18	16	32	60	6	129	790.8	81	482.4	152	173	160							
4	020.25.710	021.25.710 022.25.710	023.25.710 024.25.710	826	594	106	96	26	692	687	733	728	4	790	630	24	φ18	16	32	60	6	141	862.8	94	560.4	172	190	183							
5	020.30.800	021.30.800 022.30.800	023.30.800 024.30.800	942	658	124	114	29	777	771	829	823	6	898	702	30	φ22	20	40	80	8	120	982.4	78	619.2	284	305	300							
6	020.30.900	021.30.900 022.30.900	023.30.900 024.30.900	1042	758	124	114	29	877	871	929	923	6	998	802	30	φ22	20	40	80	8	133	1086.4	90	715.2	316	349	337							
7	020.30.1000	021.30.1000 022.30.1000	023.30.1000 024.30.1000	1142	858	124	114	29	977	971	1029	1023	6	1098	902	36	φ22	20	40	80	10	117	1198	82	814	349	396	371							
8	020.30.1120	021.30.1120 022.30.1120	023.30.1120 024.30.1120	1262	978	124	114	29	1097	1091	1148	1143	6	1218	1022	36	φ22	20	40	80	10	129	1318	93	924	394	445	429							
9	020.40.1250	021.40.1250 022.40.1250	023.40.1250 024.40.1250	1426	1074	160	150	39	1215	1214	1286	1282	5	1374	1126	40	φ26	24	48	90	12	122	1497.6	85	1012.8	709	784	746							
10	020.40.1400	021.40.1400 022.40.1400	023.40.1400 024.40.1400	1576	1224	160	150	39	1365	1364	1436	1432	5	1524	1272	40	φ26	24	48	90	12	134	1641.6	97	1156.8	787	870	850							
11	020.40.1600	021.40.1600 022.40.1600	023.40.1600 024.40.1600	1776	1424	160	150	39	1565	1564	1636	1635	5	1724	1476	45	φ26	24	48	90	14	129	1845.2	97	1349.6	899	995	979							
12	020.40.1800	021.40.1800 022.40.1800	023.40.1800 024.40.1800	1976	1624	160	150	39	1765	1764	1836	1835	5	1924	1676	45	φ26	24	48	90	14	144	2055.2	111	1545.6	1018	1147	1117							
13	020.50.2000	021.50.2000 022.50.2000	023.50.2000 024.50.2000	2215	1785	190	178	47	1965	1962	2038	2035	8	2149	1851	48	φ33	30	60	90	16	141	2300.8	107	1702.4	1586	1794	1733							
14	020.50.2240	021.50.2240 022.50.2240	023.50.2240 024.50.2240	2455	2025	190	178	47	2206	2202	2278	2275	8	2389	2091	48	φ33	30	60	120	16	156	2540.8	122	1942.4	1789	2017	1956							
15	020.50.2500	021.50.2500 022.50.2500	023.50.2500 024.50.2500	2715	2285	190	178	47	2465	2462	2538	2532	8	2649	2351	56	φ33	30	60	120	18	153	2804.4	123	2203.2	1990	2246	2164							
16	020.50.2800	021.50.2800 022.50.2800	023.50.2800 024.50.2800	3015	2585	190	178	47	2765	2762	2838	2832	8	2949	2651	56	φ33	30	60	120	18	170	3110.4	139	2491.2	2243	2553	2486							
17	020.60.3150	021.60.3150 022.60.3150	023.60.3150 024.60.3150	3428	2872	226	214	56	3104	3102	3198	3196	8	3338	2962	56	φ45	42	84	120	20	174	3536	139	2768	3762	4428	4137							

Note: Mounting Hole (n - φ) may be replaced with Screw Hole (n-M). The length of Screw Hole: T. The type of product are as follows: Type 0 (Inner and Outer Ring: φ), Type 1 (Inner and Outer Ring: M), Type 2 (Outer ring:M, Inner ring: φ), Type 3 (Outer ring:φ, Inner ring: M).