

## Tri-ROW Roller Slewing Ring (Series 13) 133.134. Internal Gear

No.	Type			Configuration & Structural Dimension										Mounting Hole Dimension						Gear Parameter						Weight					
	130	131 132	133 134	D	d	H	H1	h	130 133/134		131 132		n1	D1	D2	n	Type 0		Type 1,2,3		b	m	131 132		133 134		130	131 132	133 134		
	Steel Ball Spec. DL								D3	d1	D3	d1					Φ	M	T	z			da	z	da	kg					
1	130.25.500 (25.500)	131.25.500 132.25.500	133.25.500 134.25.500	634	366	148	138	32	474	463	537	526	4	598	402	24	Φ18	16	32	80	5 6	130 108	664 664.8	68 57	337 338.4	191	200 200	198 198			
2	130.25.560 (25.560)	131.25.560 132.25.560	133.25.560 134.25.560	694	426	148	138	32	534	523	597	586	4	658	462	25	Φ18	16	32	80	5 6	142 118	724 724.8	80 67	397 398.4	214	224 224	222 220			
3	130.25.630 (25.630)	131.25.630 132.25.630	133.25.630 134.25.630	764	496	148	138	32	604	593	667	656	4	728	532	28	Φ18	16	32	80	6 8	132 98	808.8 806.4	77 58	458.4 459.2	240	262 257	253 251			
4	130.25.710 (25.710)	131.25.710 132.25.710	133.25.710 134.25.710	844	576	148	138	32	684	673	747	736	4	808	612	28	Φ18	16	32	80	6 8	145 108	886.8 886.4	90 68	536.4 539.2	272	295 291	288 284			
5	130.32.800 (32.800)	131.32.800 132.32.800	133.32.800 134.32.800	964	636	182	172	40	770	759	841	830	4	920	680	36	Φ22	20	40	120	8 10	123 98	1006.4 1008	75 60	595.2 594	459	490 487	483 481			
6	130.32.900 (32.900)	131.32.900 132.32.900	133.32.900 134.32.900	1064	736	182	172	40	870	859	941	930	4	1020	780	36	Φ22	20	40	120	8 10	135 108	1102.4 1108	87 70	691.2 694	519	549 562	551 545			
7	130.32.1000 (32.1000)	131.32.1000 132.32.1000	133.32.1000 134.32.1000	1164	836	182	172	40	970	959	1041	1030	5	1120	880	40	Φ22	20	40	120	10 12	119 99	1218 1221.6	79 66	784 784.8	577	631 631	618 613			
8	130.32.1120 (32.1120)	131.32.1120 132.32.1120	133.32.1120 134.32.1120	1284	956	182	172	40	1090	1079	1161	1150	5	1240	1000	40	Φ22	20	40	120	10 12	131 109	1338 1341.6	91 76	904 904.8	650	710 710	698 691			
9	130.40.1250 (40.1250)	131.40.1250 132.40.1250	133.40.1250 134.40.1250	1445	1055	220	210	50	1213	1200	1300	1287	5	1393	1107	45	Φ26	24	48	150	12 14	123 105	1509.6 1509.2	83 71	988.8 985.6	1038	1137 1126	1123 1122			
10	130.40.1400 (40.1400)	131.40.1400 132.40.1400	133.40.1400 134.40.1400	1595	1205	220	210	50	1363	1350	1450	1437	5	1543	1257	45	Φ26	24	48	150	12 14	136 116	1665.6 1663.2	96 82	1144.8 1139.6	1170	1299 1281	1254 1258			
11	130.40.1600 (40.1600)	131.40.1600 132.40.1600	133.40.1600 134.40.1600	1795	1405	220	210	50	1563	1550	1650	1637	6	1743	1457	48	Φ26	24	48	150	14 16	131 114	1873.2 1868.8	96 84	1335.6 1334.4	1341	1501 1471	1454 1448			
12	130.40.1800 (40.1800)	131.40.1800 132.40.1800	133.40.1800 134.40.1800	1995	1605	220	210	50	1763	1750	1850	1837	6	1943	1657	48	Φ26	24	48	150	14 16	145 127	2069.2 2076.8	110 96	1531.6 1526.4	1518	1682 1697	1658 1663			
13	130.45.2000 (45.2000)	131.45.2000 132.45.2000	133.45.2000 134.45.2000	2221	1779	231	219	54	1967	1945	2055	2033	6	2155	1845	60	Φ33	33	60	160	16 18	141 125	2300.8 2300.4	107 95	1702.4 1699.2	1494	2147 2129	2114 2112			
14	130.45.2240 (45.2240)	131.45.2240 132.45.2240	133.45.2240 134.45.2240	2461	2019	231	219	54	2207	2185	2295	2273	6	2395	2085	60	Φ33	33	60	160	16 18	157 139	2556.8 2552.4	121 108	1926.4 1933.2	2197	2501 2461	2447 2407			
15	130.45.2500 (45.2500)	131.45.2500 132.45.2500	133.45.2500 134.45.2500	2721	2279	231	219	54	2467	2445	2555	2533	8	2655	2345	72	Φ33	33	60	160	18 20	154 138	2822.4 2816	122 110	2185.2 2188	2590	2786 2731	2862 2834			
16	130.45.2800 (45.2800)	131.45.2800 132.45.2800	133.45.2800 134.45.2800	3021	2579	231	219	54	2767	2745	2855	2833	8	2955	2645	72	Φ33	33	60	160	18 20	170 153	3110.4 3116	139 125	2491.2 2488	2932	3061 3079	3211 3209			
17	130.50.3150 (50.3150)	131.50.3150 132.50.3150	133.50.3150 134.50.3150	3432	2868	270	258	65	3104	3090	3213	3196	8	3342	2958	72	Φ45	42	84	180	20 22	174 158	3536 3537.6	139 126	2768 2758.8	4551	5025 5009	4954 4988			

Note: Mounting Hole (n - Φ) may be replaced with Screw Hole (n-M). The length of Screw Hole: T. The type of product are as follows: Type 0 (Inner and Outer Ring: Φ), Type 1 (Inner and Outer Ring: M), Type 2 (Outer ring:M, Inner ring: φ), Type 3 (Outer ring: φ, Inner ring: M).

**CHANGZHOU AOXUAN HEAVY BEARING CO.,LTD.**

ADD:NO.158, Xinyuan 3<sup>RD</sup> Road, Xinbei District, Changzhou, Jiangsu, China

<https://aoxuanbearing.com>